

MIN. 6" (152.4 mm) WIDE APPROVED
FIRESTONE UNDERLAYMENT

APPROPRIATE FIRESTONE FASTENER
8" (203.2 mm) O.C. MAX.

3/16" x 7/8" (4.8mm x 63.5 mm)
DOUBLE BEAD BUTYL TAPE

APPROPRIATE FIRESTONE FASTENER
8" (203.2 mm) O.C. MAX.

EAVE STARTER FLASHING

FIRESTONE APPROVED
UNDERLAYMENT

GUTTER

WOOD NAILER (SEE NOTES)

FIRESTONE INSULATION
(OPTIONAL)
SUBSTRATE

NOTES:

1. REFER TO FIRESTONE WEBSITE FOR MOST CURRENT INFORMATION.
2. REFER TO TECHNICAL INFORMATION SHEETS FOR FASCIA SIZES, ACCESSORIES, AND FINISHES AVAILABLE.
3. WOOD NAILER MUST BE INSTALLED TO MEET APPLICABLE BUILDING CODES OR 200 LBS PER LINEAR FOOT MINIMUM IN ANY GIVEN DIRECTION.
4. REFER TO THE FIRESTONE TECHNICAL DATABASE FOR FASTENER COMPATIBILITY WITH METAL.
5. REFER TO THE FIRESTONE TECHNICAL DATABASE FOR HEM LENGTH AND REQUIRED DISTANCE BETWEEN THE PANEL AND CLEAT.
6. APPLICATION DETAILS ARE FOR ILLUSTRATION PURPOSES ONLY AND MAY NOT BE APPROPRIATE FOR ALL BUILDING DESIGNS AND CONDITIONS.

FOR WARRANTY PERIODS GREATER THAN
20 YEARS REFER TO METAL QUICK SPECS
FOR MINIMUM REQUIREMENTS.

MAXIMUM WARRANTY: 20 YEARS

Firestone
BUILDING PRODUCTS
NOBODY COVERS YOU BETTER.™
www.firestonebpco.com

SLIDING EAVE AT GUTTER

UNA-CLAD®

ACCEPTABLE SYSTEMS: UC3-RS

ISSUE / REVISION
DATE:

08-22-2013

NOT TO SCALE

DETAIL NO.

3-E-2