



- NOTES:
1. INSERT SHALL EXTEND MINIMUM 3" (76.2 mm) INTO DRAIN PIPE BEYOND SEAL OF EXISTING DRAIN AND SEAL TO INTERIOR OF PIPE BY MEANS OF A MECHANICAL SEAL. A MECHANICAL SEAL IS ACHIEVED BY EITHER EXPANDING A MALLEABLE INSERT TUBE IN A BED OF SEALANT TO FORM A COMPRESSION SEAL TO THE PLUMBING PIPE OR BY A MECHANICAL EXPANSION DEVICE ATTACHED TO THE INSERT TUBE.
 2. IN EITHER CASE THE PERFORMANCE OF THE INSERT IS THE RESPONSIBILITY OF THE SPECIFIER AND COMPONENT MANUFACTURER. COMPRESSION RING MUST BE MINIMUM 1" (25.4 mm) WIDE WITH DULL EDGES.

MAXIMUM WARRANTY: **N/A**

DRAIN INSERT



DRAIN INSERT	
GEOGARD™	ACCEPTABLE SYSTEMS: EPDM, EPDM-R, ECOWHITE EPDM

ISSUE / REVISION DATE: 7-28-2015

DETAIL NO. D-2

NOT TO SCALE