



## QuickScrubber Plus™ Primer Application System

**Firestone Item Number:**  
**W563582049: QuickScrubber Plus  
Holder and Pads**

### DESCRIPTION:

QuickScrubber Plus Primer Application System consists of a scrub pad and holder that allows application of QuickPrime™ Plus from a standing position. The QuickScrubber Plus scrub pad is secured in place to the bottom of the holder and has a fitting to accept an extension handle (handle not included). The pads for the QuickScrubber Plus system are included with each kit.

The bottom-bearing surface of the QuickScrubber Plus holder is slightly concave. When proper pressure is applied, the handle flattens out assuring that proper pressure is maintained.

### METHOD OF APPLICATION:

Install a QuickScrubber Plus pad on the bottom of the handle by pressing the pad onto the Velcro® strips with firm hand pressure. Use back and forth strokes with heavy pressure along the length of the splicing area, until membrane surface becomes dark gray in color with no streaking or puddling.

Bear down on the QuickScrubber Plus pad and handle system during application so the pad holder flattens to allow the total surface to contact with the priming surface. Each pad will prime about 30.5 m - 61.0 m (100.0' - 200.0') by 152.4 mm - 177.8 mm (6.0" - 7.0") wide area. Change pads routinely. Do not attempt to turn pads over and re-use: discard after 30.5 m - 61.0 m (100.0' - 200.0') of priming.

Note: Additional application instructions on the use of QuickPrime Plus and QuickScrubber Plus can be found on the QuickPrime Plus Technical Information Sheet and in Firestone's Specification Manual.



## PRODUCT DATA

Property	Minimum Performance
<b>QuickScrubber Plus Handle</b>	
Handle Base:	High quality plastic, with slight camber (upward bow)
Color:	Red
Pad Holding Mechanism:	Industrial grade Velcro® strips
Handle acceptor:	Standard broom thread with swivel
<b>QuickScrubber Plus Pad</b>	
Base:	Nylon fibers with abrasive grain bound with solvent resistant resins
Dimensions:	88.9 mm x 177.8 mm x 1.27 mm (3.5" x 7.0" x 0.5")
Color:	Gray
Grit:	240
Weight:	993 gm (35 oz)

### PACKAGING:

QuickScrubber Plus handles and pads are packaged with various QuickSeam™ products as follows:

Product	QuickPrime Plus Scrub Handle/Pad			
	QS + holder	QS + pads	Std. QS holder	Std. QS pads
76.2 mm (3.0") QuickSeam Tape	1	3	1	3
152.4 mm (6.0") & 177.8 mm (7.0") QuickSeam Tape	1	1	1	1
152.4 mm (6.0") QuickSeam Batten Cover	1	2	n/a	n/a
127 mm (5.0") QuickSeam Flashing	1	2	n/a	n/a

QuickScrubber Plus kits are also available and contain 4 handles and 20 pads per carton; 144 cartons per pallet.

### PRECAUTIONARY DATA:

Keep pads clean and dry prior to use.

Note: QuickScrubber Plus is protected under U.S. Patent Number 5,976,292.

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice design, Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any project on which its products may be applied. If questions arise as to the soundness of a project, or its ability to support a planned installation property, the Owner should obtain opinions of competent design engineers before proceeding. Firestone accepts no liability for any failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

**Firestone Specialty Products**  
250 West 96th Street, Indianapolis, Indiana 46260  
Specialty Products (800) 428-4442  
Internet Address: <http://www.firestonesp.com>