

TECHNICAL INFORMATION SHEET

QuickSeam™ Flashing

Item Description

5" x 100' (127 mm x 30.5 m)

Item Number

W56RAC1615



Product Information

Description:

QuickSeam Flashing is a semi-cured EPDM flashing laminated to cured seam tape; used to flash gravel stops and other details as specified in Firestone Specifications and Details.

Method of Application:

1. Use QuickPrime™ Plus and QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime membrane and metal mating surfaces.
2. Refer to Firestone Specifications and Details.
3. Refer to application instructions for specifics: www.firestonebpc.com.

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

Shelf Life:

- Shelf life of one year can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Precautions:

- Refer to Safety Data Sheet (SDS).
- QuickSeam Flashing is semi-cured. Do not stretch.

LEED® Information:

Post-Consumer Recycled Content: 0%
Post Industrial Recycled Content: 0%
Manufacturing Location: Prescott, AR

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.



TECHNICAL INFORMATION SHEET

QuickSeam™ Flashing

Packaging:

- 2 – 5" (127 mm) x 100' (30.5 m) rolls per carton (Rolls may consist of two separate sections of QuickSeam Flashing to make 100')
- 36 cartons per pallet

NOTE: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

Typical Properties

QUICKSEAM TAPE		FLASHING MATERIAL	
Property	Test Method	Property	Test Method
Base	Rubber Polymers	Base	EPDM
Color	Black	Color	Black
Solvents	None	Solvents	None
Solids	100%	Solids	100%
Cured State	Cured	Cured State	Semi-Cured
Thickness	0.045" (1.14 mm) ± 0.005" (0.13 mm)	Thickness	0.045" (1.14 mm) ± 10%
Width	5¼" (133.4 mm) + 0, - 1/16"	Width	5" (127 mm) + 0, - 1/8"
Length	100' (30.5 m)		

Please contact Firestone Technical Services Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.