

QuickSeam™ Batten Cover

Item Description

6" x 100'
9" x 100'
12" x 50'

Item Number

W56RAC1616
W56RAC1619
W56RAC1624



Product Information

Description:

QuickSeam Batten Cover is a semi-cured EPDM and QuickSeam Tape laminate designed to cover and seal batten strips and as specified by Firestone Specifications and Details. The release paper has been perforated, resulting in centering marks on the tape which acts as a guide in the application of the QuickSeam Batten Cover.

Method of Application:

1. Use QuickPrime™ Plus and QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime the membrane and metal components within the seaming area.
2. Use the centering marks on the tape as a guide to apply the QuickSeam Batten Cover Strip over the batten strip.
3. Refer to application instructions for specifics: Technical Database, www.firestonebpc.com

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of one year can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Precautions:

Refer to Safety Data Sheet (SDS).

LEED® Information:

Post Consumer Recycled Content: 0%
Post Industrial Recycled Content: 0%
Manufacturing Location: Prescott, AR

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.



Packaging:

6" Roll - 2 rolls per carton – 36 cartons per pallet
9" Roll - 1 roll per carton – 36 cartons per pallet
12" Roll - 1 roll per carton – 36 cartons per pallets

QuickSeam™ Batten Cover

Typical Properties

QuickSeam Tape		EPDM Flashing	
Property	Value	Property	Value
QuickSeam Tape:	Rubber Polymers	Base	EPDM
Base	Black	Color	Black
Color	None	Solvents	None
Solvents	100%	Solids	100%
Solids	98± 0.02 (H ₂ O = 1)	Cured State	Semi-Cured
Specific Gravity	Cured	Thickness	0.040"(1.016 mm) ± 0.017"- 0.007"
Cured State	0.035" (0.89 mm) ± 0.005" (0.127 mm)	Width	6"+ 0, - 0.["
Thickness	6[" (15.56cm) + 0.95cm, - 0"		

Please contact Quality Building Services Technical Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.