

# TECHNICAL INFORMATION SHEET

## QuickSeam™ FormFlash

TIS #1405

**ITEM NUMBER:**

- 9" W56RAC1650
- 12" W56RAC1653
- 18" W56RAC162A



**Description:**

QuickSeam FormFlash consists of uncured FormFlash factory laminated to QuickSeam Tape. It is designed to flash inside and outside corners, pipes, penetration pockets and other applications as required by Firestone Specifications and Details.

**Method of Application:**

1. Use QuickPrime™ Plus and a QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime mating surfaces. Refer to Firestone Installation Instruction Sheet for QuickSeam FormFlash (included in each carton) and Firestone Specifications and Details.
2. When cloudy conditions below 60 °F (15.6 °C) occur, use heat guns (without ignition sources) to heat QuickSeam FormFlash. This will ensure good formability of the QuickSeam FormFlash to the primed substrate.
3. On sunny days less than 70 °F (21.1 °C), place QuickSeam FormFlash on roof (prior to application) with flashing side up to allow QuickSeam FormFlash to warm to ensure good formability.
4. On sunny days greater than 70 °F (21.1 °C), place QuickSeam FormFlash on roof (prior to application) with release paper side up to prevent QuickSeam FormFlash from gaining too much heat and to ensure good formability.
5. Refer to application instructions for specifics: Technical Database, [www.firestonebpco.com](http://www.firestonebpco.com)

**Storage:**

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of one year can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

**Precautions:**

- Refer to Material Safety Data Sheet (MSDS).

**Compliance:**

Post Consumer Recycled Content: 0%  
 Pre Consumer Recycled Content: 0%  
 Manufacturing Location: Prescott, AR

**Packaging:**

Roll	9"x50'	2 rolls per carton	40 cartons per pallet
	12"x50'	1 roll per carton	36 cartons per pallet
	18"x50'	1 roll per carton	24 cartons per pallet

**NOTE:** QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

# TECHNICAL INFORMATION SHEET



Physical Properties:	Value	Physical Properties:	Value
QuickSeam Tape:		EPDM Flashing:	
Base	Rubber Polymers	Base	EPDM
Color	Black	Color	Black
Solvents	None	Solvents	None
Solids	100%	Solids	100%
Cured State	Cured	Cured State	Uncured
Thickness	0.025" (0.635 mm) ± 0.007" (0.18 mm)	Thickness	0.065" (1.6 mm) ± 0.005" (0.13 mm)

Please Contact your Firestone Roof Systems Advisor at 1-800-428-451:

*This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.*