

# TECHNICAL INFORMATION SHEET

## QuickSeam™ Pipe Flashing



**Item Description**

Black Molded Pipe Flashing

**Item Number**

W563581063

### Product Information

#### Description:

QuickSeam Pipe Flashings are specifically designed to be used in roofing applications for flashing of round penetrations. QuickSeam Pipe Flashings will fit various penetrations and must be cut to correct pipe diameter before installation. QuickSeam Pipe Flashings may be used to flash penetrations for both RubberGard™ EPDM as well as APP and SBS Modified Bitumen systems. Refer to Firestone details MB-P-5 for use with APP.

#### Method of Application:

1. Clean the RubberGard membrane using QuickPrime™ Plus, QuickPrime Plus LVOC, Single Ply QuickPrime Primer or Single Ply LVOC Primer using a QuickScrubber™ or QuickScrubber Plus pad and handle to remove all dusting agents, dirt and other contaminants that will affect the finished bond.
2. Allow to dry per the touch-push test.
3. Cut along the top edge of the ring on the QuickSeam Pipe Flashing corresponding to the size of the pipe.
4. Remove the release liner from the tape portion.
5. Install the pipe flashing and roll the flange with a silicone hand roller.
6. Install the clamping ring and Lap Sealant per Firestone Specifications and Details.
7. Install per specific requirements as outlined on the QuickSeam Pipe Flashing Technical Information Sheet located in the Firestone Asphalt Technical Manual.

#### Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

#### Shelf Life:

- Shelf life of two years can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

#### Packaging:

10 Flashing, 10 Stainless Steel champs per carton

#### Precautions:

- Do not install on uneven substrates.
- Refer to Safety Data Sheet (SDS).

# TECHNICAL INFORMATION SHEET

## QuickSeam™ Pipe Flashing

### LEED® Information:

Post Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Bensenville, IL

\*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

### Fit Guidelines: Fits the pipe outside diameters

1.000" - 1.375"	25.4 mm – 34.9 mm
1.625" - 1.875"	41.3 mm – 47.6 mm
2.000" – 2.625"	50.8 mm – 66.7 mm
2.750" – 3.625"	69.8 mm – 92.1 mm
4.000" – 4.500"	102.0 mm – 114.0 mm
5.000" – 5.563"	127.0 mm – 141.0 mm
6.000" – 6.875"	152.4 mm – 174.6 mm

NOTE: For penetrations less than 1" in diameter, use Firestone QuickSeam Conduit Flashing.

### Typical Properties

Property	Value
<b>Molded Pipe Flashing:</b>	
Base	Molded EPDM
Color	Black
Sizes	Universal – Fits 1" O.D. to 6.875" O.D. (25.4 mm to 174.6 mm)
Clamp	Stainless Steel – worm gear type (clamps are included)
Pipe Flange	13" (33 cm) outside diameter
Thickness	0.055"-0.075" (1.4 mm – 1.9 mm)
<b>QuickSeam Tape:</b>	
Base	Rubber Polymer
Color	Black
Solvents	None
Percent Solids	100%
Cured State	Cured
Thickness	0.030" (0.762 mm) + 0.005" (0.13 mm)

Please contact Quality Building Services Technical Department at 1-800-428-4511 for further information.

*This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.*