

QuickSeam™ Conduit Flashing

Item Description

Various sizes from ½" to 2 ½"

Item Number

W563581070



Product Information

Description:

Firestone QuickSeam Conduit Flashing is designed to be used in roofing applications for flashing of rigid round penetrations and conduit. QuickSeam Conduit Flashing will fit various size penetrations from ½" to 2 ½" (12.7 mm to 63.5 mm) and can be cut to desired diameter before installation.

QuickSeam Conduit Flashing may be used to flash small diameter penetrations and conduit for RubberGard™ EPDM as well as APP and SBS modified bitumen systems. On modified bitumen systems, a target patch of smooth APP must first be installed per Firestone's details.

Method of Application:

1. Penetration must be clean of old flashings and foreign materials.
2. Cut along the top edge of the ring on the QuickSeam Conduit Flashing corresponding to the size of pipe or conduit.
3. Clean the RubberGard membrane using QuickPrime™ Plus, QuickPrime Plus LVOC, Single-Ply QuickPrime Primer or Single-Ply LVOC Primer applied with a QuickScrubber™ or QuickScrubber Plus pad and handle to remove all dusting agent, dirt and other contaminants affecting the finished bond.
4. Allow to dry according to the touch-push test.
5. Remove the release paper.
6. Install the pipe flashing and roll the flange with a silicone hand roller.
7. Install the clamping ring and Lap Sealant per Firestone Specifications and Details.
8. Modified Bitumen Membrane Preparation: Install per specific requirements as outlined on the QuickSeam Pipe Flashing Technical Information Sheet located in the Firestone Asphalt Technical Manual.

Precautions:

- Do not install on uneven substrates.
- Refer to Safety Data Sheet (SDS).

Shelf Life:

- Shelf life of two years can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

LEED® Information:

Post Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Bensenville, IL

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

QuickSeam™ Conduit Flashing

Fit Guidelines

½" (12.7 mm)	1 ¾" (45.0 mm)
¾" (19.0 mm)	2" (51.0 mm)
1" (25.4 mm)	2 ¼" (57.15 mm)
1 ¼" (32.0 mm)	2 ½" (64.0 mm)
1 ½" (37.0 mm)	

Typical Properties

Property	Value
Molded Pipe Flashing:	
Base	Molded EPDM
Color	Black
Clamp	Stainless Steel – worm gear type (clamps are included)
Pipe Flange	9" (229 mm) outside diameter
Thickness	0.055" – 0.075" (1.4 mm -1.9 mm)

QuickSeam Tape:

Base	Rubber Polymer
Color	Black
Solvents	None
Percent Solids	100%
Cured State	Cured
Thickness	0.030" (0.762 mm) + 0.005" (0.13 mm)

Please contact Quality Building Services Technical Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.