

EcoWhite™ QuickSeam™ Pipe Flashing

Item Description
White Pipe Boots

Item Number
W56358106A

Product Information

Description:

Firestone EcoWhite EPDM QuickSeam Pipe Flashings are specifically designed to be used in roofing applications for flashing of round penetrations. EcoWhite EPDM QuickSeam Pipe Flashings will fit various penetrations and must be cut to correct pipe diameter before installation.

EcoWhite EPDM QuickSeam Pipe Flashings may be used to flash penetrations for the RubberGard EcoWhite EPDM fully adhered systems.

Method of Application:

1. Clean and prime the RubberGard EcoWhite membrane to receive the tape flange using Single-Ply QuickPrime™ Primer or Single-Ply QuickPrime LVOC Primer with a QuickScrubber™ or QuickScrubber Plus pad and handle to remove all dusting agent, dirt and other contaminants affecting the finished bond.
2. Allow Primer to dry per the touch-push test.
3. Cut along the top edge of the ring on the EcoWhite EPDM QuickSeam Pipe Flashing corresponding to the size of the pipe.
4. Remove the release liner from tape.
5. Install the pipe flashing and roll the flange with a silicone hand roller.
6. Install the clamping ring and EcoWhite EPDM Lap Sealant Seam Edge Treatment per Firestone Specifications.
7. Refer to application instructions for specifics: Technical Database, www.firestonebpc.com

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of two years can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).

Shelf Life:

Shelf life will be shortened if exposed to elevated temperatures

Packaging:

Each carton contains 10 Pipe Boots.

Precautions:

- Do not install on uneven substrates.
- Refer to Safety Data Sheet (SDS).

TECHNICAL INFORMATION SHEET

EcoWhite™ QuickSeam™ Pipe Flashing

LEED® Information:

Post Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 0%
 Manufacturing Location: Michigan Center, MI
 *NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Fit Guidelines- Make Cut Above Rib

Fits the pipe outside diameter listed below	
Pipe Size	Diameter
1.000"	25.4 mm
1.500"	38.1 mm
2.000"	50.8 mm
3.000"	76.2 mm
4.000"	102.0 mm
5.000"	127.0 mm
6.000"	152.4 mm

Typical Properties

Molded Pipe Flashing	
Property	Value
1.000"	25.4 mm
1.500"	38.1 mm
2.000"	50.8 mm
3.000"	76.2 mm
4.000"	102.0 mm
5.000"	127.0 mm
QuickSeam Tape	
Base	Rubber Polymer
Color	White
Solvents	None
Percent Solids	100%
Cured State	Cured
Thickness	0.030" (0.762 mm) + 0.005" (0.13 mm)

Please contact Quality Building Services Technical Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.