

QuickSeam™ SA Patch for Pipe Flashing

Item Description

18" x 18"

Item Number

W56RAC1629

Product Information

Description:

RubberGard™ QuickSeam SA Patch for Pipe Flashing ("QS SA Patch for Pipe Flashing") consists of 18" X 18" Standard RubberGard EPDM membrane fully and completely factory laminated to QuickSeam tape with a 7¼" diameter hole die-cut in the center. It can be used to flash the flange of QuickSeam Pipe Boots in conjunction with RubberGard EPDM roofing systems where allowed by Firestone specifications.

QuickSeam tape is used as the tape adhesive to field splice QS SA Patch for Pipe Flashing to primed flanges of QuickSeam Pipe Boot and RubberGard membrane. The polymeric release liner protects the tape until field application, and is perforated to allow removal of the liner in separate sections.

Method of Application:

1. Prime all surfaces (membrane and flanges) to receive QS SA Patch for Pipe Flashing using QuickPrime™ Plus Primer; QuickPrime Plus LVOC Primer; Single-Ply QuickPrime; or QuickPrime Plus LVOC Primer scrub applied with QuickScrubber™ Pad and Handle.
2. Allow primer to flash off. Use Touch-Push test to verify primer readiness.
3. Remove release liner in sections to mate QS SA Patch for Pipe Flashing to primed substrates only when QS SA Patch for Pipe Flashing is properly positioned over primed substrate.
4. Roll the freshly mated QS SA Patch for Pipe Flashing with silicone coated rubber hand roller to ensure proper mating.
5. Apply seam edge treatment at all lap edges of the QS SA Patch for Pipe Flashing: the perimeter and the die-cut center hole.
6. Refer to Application Instructions included in each cartons for specifics.

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of two years can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

LEED® Information:

Post Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Michigan Center, MI

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Packaging:

- 25 Pieces per Carton
- 20 Cartons per Pallet

TECHNICAL INFORMATION SHEET

QuickSeam™ SA Patch for Pipe Flashing

Precautions:

Refer to Safety Data Sheet (SDS) for more information.

Typical Properties

<u>Property</u>	<u>Value</u>
QuickSeam Tape:	
Base	Rubber Polymers
Color	Black
Solvents	None
Solids	100%
Cured State	Cured
Thickness	0.020" (0.508 mm) ± 0.005" (0.127 mm)
Dimensions	18" x 18" (457.2 mm x 457.2 mm) with 7¼" (184.1 mm) diameter center hole
Membrane:	
Base	EPDM, Non-reinforced
Color	Black
Solvents	None
Cured State	Cured
Thickness	0.060" (1.52 mm) ± 0.005" (0.127 mm)
Width	18" x 18" (457.2 mm x 457.2 mm) with 7¼" (184.1 mm) diameter center hole
Release Liner :	The tape portion of QS SA Patch for Pipe Flashing is protected by polymeric release liner, perforated to allow removal in separate sections to facilitate application.

Please contact Quality Building Services Technical Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.