

TECHNICAL INFORMATION SHEET

Una-Clad UC-7 Clip

Item Description

Galvanized Steel
Stainless Steel

Item Number

W6810C0700G
W6810C0700S



Product Information

Description:

Firestone UNA-CLAD UC-7 Clips are specially designed to be used in the attachment of the Firestone UNA-CLAD UC-7 Standing Seam Roof Panel. The design of the clip allows unlimited thermal movement of the panel while securing the UC-7 Snap-On-Batten.

Method of Application:

1. Position the clips flush against the vertical seam.
2. Attach clips to roof deck using the appropriate Firestone fastener.
3. Position adjacent panel flush against installed clip.
4. Secure panel by folding clip tabs over the vertical seam.

NOTE: Install assembly according to Firestone Metal Design and Application Guides found on the Firestone website. Follow approved installation details.

Storage:

Store in unopened original containers protected from the weather.

Packaging:

100 clips per carton

Precautions:

- Do not overdrive or underdrive fastener.
- Clips are designed to anchor UC-7 standing seam roof panels only
- Can not be used with Firestone HD Plus Fasteners or fasteners larger than #15.
- Eye protection must be worn during the installation of fasteners.
- Refer to Safety Data Sheets (SDS) for safety information.

Stocking Location:

Anoka, MN



Una-Clad UC-7 Clip

Typical Properties

<u>Property</u>	<u>Minimum Performance</u>
Material	G-90 Galvanized Steel 300 Series Stainless Steel
Material Thickness Galvanized Steel	24 ga; 0.031" (0.79 mm) 3.0" x 1.625" (76.20 mm x 41.28 mm)
Stainless Steel	26 ga; 0.024" (0.61 mm) 3.0" x 1.625" (76.20 mm x 41.28 mm)
Base	5.0" x 1.0" (127.0 x 25.40 mm)
Tab	3.0" x 1.25" (76.20 x 31.75 mm)
Hole Diameter	0.25" (6.35 mm)

Please contact Quality Building Services Technical Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.