

TECHNICAL INFORMATION SHEET

EcoWhite™ QuickSeam™ Corner Flashing

TIS #1432

ITEM NUMBER: W56RACEWCF

Description:

Firestone EcoWhite EPDM QuickSeam Corner Flashing consists of Firestone flashing factory laminated to QuickSeam Tape. It is 8.5" (216 mm) in diameter and is designed to flash inside and outside corners in conjunction with EcoWhite EPDM Roof Systems.



Method of Application:

1. Use Single-Ply QuickPrime™ Primer or Single-Ply QuickPrime™ LVOC Primer with a QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime mating surfaces.
2. Refer to Firestone Installation Instruction Sheet for EcoWhite EPDM QuickSeam Corner Flashing (included in each carton) and Firestone Specifications and Details.
3. When cloudy conditions below 60 °F (15.6 °C) occur, use heat guns (without ignition sources) to heat EcoWhite EPDM QuickSeam Corner Flashing. This will ensure good formability of the EcoWhite EPDM QuickSeam Corner Flashing to the primed substrate.
4. On sunny days less than 70 °F (21.1 °C), place EcoWhite EPDM QuickSeam Corner Flashing on roof (prior to application) with flashing side up to allow EcoWhite EPDM QuickSeam Corner Flashing to warm to ensure good formability.
5. On sunny days greater than 70 °F (21.1 °C), place EcoWhite EPDM QuickSeam Corner Flashing on roof (prior to application) with release paper side up to prevent EcoWhite EPDM QuickSeam Corner Flashing from gaining too much heat and to ensure good formability.
6. Refer to application instructions for specifics: Technical Database, www.firestonebpco.com

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 100 °F (37.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of 6 months can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Precautions:

- Refer to Material Safety Data Sheet (MSDS).

Compliance:

Post Consumer Recycled Content: 0%
Pre Consumer Recycled Content: 0%
Manufacturing Location: Michigan Center, MI

Packaging:		
Units	20 units per carton	100 cartons per pallet

Physical Properties:	Value	Physical Properties:	Value
QuickSeam Tape:		FormFlash:	
Base	Rubber Polymers	Base	EPDM
Color	White	Color	White
Solvents	None	Solvents	None
Solids	100%	Solids	100%
Cured State	Cured	Cured State	Semi-cured
Thickness	0.025" (0.64 mm) ± 0.005" (0.127 mm)	Thickness	0.060" (1.59 mm) ± 0.005" (0.127mm)

Please Contact your Firestone Roof Systems Advisor at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.