



ACCEPTABLE SA LAP SPLICE DETAIL

3" RUBBERGARD EPDM SA MEMBRANE FLAP

3" (76 mm) MIN.

CONTINUOUS BEAD OF
LAP SEALANT (SEE NOTE #2)

QUICKSEAM CORNER FLASHING
(CENTERED IN CORNER)

5" QUICKSEAM FLASHING
(CENTERED OVER QUICKSEAM
CORNER FLASHING)

**USE APPROPRIATE
TERMINATION DETAIL**

**USE APPROPRIATE
BASE TIE-IN**

RUBBERGARD EPDM SA MEMBRANE

2" (50 mm)

3" (76 mm) MIN.

- NOTES:
1. REFER TO FIRESTONE WEBSITE FOR THE MOST CURRENT INFORMATION.
 2. APPLY LAP SEALANT ON CUT EDGES OF REINFORCED MEMBRANE AND PERIMETER OF QUICKSEAM FLASHING AS SHOWN. REFER TO LS-9 FOR SEAM EDGE TREATMENT.
 3. REFER TO C-4a FOR DETAILED INSTALLATION INSTRUCTIONS
 4. USE APPROPRIATE FIRESTONE PRIMER TO CLEAN AND PRIME EPDM MATING SURFACES PRIOR TO INSTALLATION OF QUICKSEAM PRODUCTS.

MAXIMUM WARRANTY: **20 YEARS**

INSIDE CORNER WITH 3" FLAP

RUBBERGARD™ EPDM SA

ACCEPTABLE SYSTEMS: EPDM SA

ISSUE / REVISION
DATE:

8/18/2017

DETAIL NO.

EPDM SA C-4