



FIRESTONE BUILDING PRODUCTS

2014 LTTR VALUES

Long-Term Thermal Resistance - Polyiso Board Stock Insulation

SIZE	R-VALUE	PSC
0.5	2.9	96
1.0	5.7	48
1.1	6.3	42
1.2	6.8	40
1.3	7.4	36
1.4	8.0	34
1.5	8.6	32
1.6	9.1	30
1.7	9.7	28
1.8	10.3	26
1.9	10.8	25
2.0	11.4	24
2.1	12.0	22
2.2	12.6	21
2.3	13.2	20
2.4	13.8	20
2.5	14.4	19
2.6	15.0	18
2.7	15.6	17
2.8	16.2	17
2.9	16.8	16
3.0	17.4	16
3.1	18.0	15
3.2	18.6	15
3.3	19.2	14
3.4	19.9	14
3.5	20.5	13
3.6	21.1	13
3.7	21.7	12
3.8	22.3	12
3.9	23.0	12
4.0	23.6	12

BASED ON ASTM C1289-13e1	
R-Value	Thickness
20.0	2 layers 1.8" (R-20.6)
25.0	2 layers 2.2" (R-25.2)
30.0	2 layers 2.6" (R-30.0)
35.0	2 layers 3.1" (R-36.0)
40.0	2 layers 3.5" (R-41.0)

For more information, contact your local Sales Rep or visit
FIRESTONEBPCO.COM.

200 4th Ave. S., Nashville, TN 37201
CORPORATE OFFICE: (800) 428-4442

[/FirestoneBuildingProducts](https://www.facebook.com/FirestoneBuildingProducts) [@FirestoneBPCo](https://twitter.com/FirestoneBPCo)

Firestone

Firestone Building Products

©2014 Firestone Building Products Updated 0618