



# FIRESTONE BUILDING PRODUCTS

## 2014 LTTR VALUES

### Long-Term Thermal Resistance - Polyiso Board Stock Insulation

SIZE	R-VALUE	PSC
0.5	2.9	96
1.0	5.7	48
1.1	6.3	42
1.2	6.8	40
1.3	7.4	36
1.4	8.0	34
1.5	8.6	32
1.6	9.1	30
1.7	9.7	28
1.8	10.3	26
1.9	10.8	25
2.0	11.4	24
2.1	12.0	22
2.2	12.6	21
2.3	13.2	20
2.4	13.8	20
2.5	14.4	19
2.6	15.0	18
2.7	15.6	17
2.8	16.2	17
2.9	16.8	16
3.0	17.4	16
3.1	18.0	15
3.2	18.6	15
3.3	19.2	14
3.4	19.9	14
3.5	20.5	13
3.6	21.1	13
3.7	21.7	12
3.8	22.3	12
3.9	23.0	12
4.0	23.6	12

BASED ON ASTM C1289-13e1	
R-Value	Thickness
20.0	2 layers 1.8" (R-20.6)
25.0	2 layers 2.2" (R-25.2)
30.0	2 layers 2.6" (R-30.0)
35.0	2 layers 3.1" (R-36.0)
40.0	2 layers 3.5" (R-41.0)

For more information, contact your local Sales Rep or visit  
[FIRESTONEBPCO.COM](http://FIRESTONEBPCO.COM).

250 WEST 96<sup>TH</sup> ST., INDIANAPOLIS, IN 46260  
CORPORATE OFFICE: (800) 428-4442 • (317) 575-7000

 /FirestoneBuildingProducts

 @FirestoneBPCo

**Firestone**  
BUILDING PRODUCTS  
**NOBODY COVERS YOU BETTER.™**

©2014 Firestone Building Products Updated 0414