

TECHNICAL INFORMATION SHEET

Ceramic Coated Roofing Granules



Item Description

White
Black

Item Number

W70RACGGWH
W70RACGGBK

Product Information

Description:

Ceramic coated roofing granules are made available in 50 lb (22.7 kg) metal pails.

Method of Application:

Firestone recommends that granules be applied to areas of asphalt "bleed-out" while the asphalt is still in a molten state. Areas of "bleed-out" at inside and outside corners require application of granules.

Precautions:

- Minimize the amount of dust generated when applying or handling this product. Use in well ventilated area.
- Review the Safety Data Sheet (SDS) for more information.

LEED® Information:

Post Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Beech Grove, IN

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Packaging

<u>Property</u>	<u>Value</u>
Pail	5 Gallon (18.9 L)
Weight	50 lb (22.7 kg)
Pallet Size	48" x 39" (1.2 m x 1.0 m)
Pails per Pallet	36
Pallet Weight	2000 lb (907 kg)
Pallets per Truckload	24

Please contact Quality Building Services Technical Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.