

Safety Data Sheet

Firestone Building Products Company

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name • **FillGard™ M Pourable Sealer Part A**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s) • Construction

1.3 Details of the supplier of the safety data sheet

Manufacturer • Firestone Building Products Company

200 4th Avenue S
Nashville, TN 37201-2208
United States

firestonemsds@bfdp.com

Telephone (General) • 800-428-4442

1.4 Emergency telephone number

Manufacturer • (800) 424-9300 - CHEMTREC

Manufacturer • (703) 527-3887 - CHEMTREC - International

Section 2: Hazards Identification

EU/EEC

According to: Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]

According to: EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

- CLP**
- Skin Irritation 2 - H315
 - Skin Sensitization 1 - H317
 - Eye Irritation 2 - H319
 - Acute Toxicity Inhalation 4 - H332
 - Respiratory Sensitization 1 - H334
 - Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation - H335
 - Carcinogenicity 2 - H351
 - Specific Target Organ Toxicity Repeated Exposure 2 - H373
- DSD/DPD**
- Harmful (Xn)
 - Irritant (Xi)
 - Carcinogenic Substances - Category 3
 - R20, R36/37/38, R40, R42/43, R48/20

2.2 Label Elements

CLP

DANGER



- Hazard statements** • H315 - Causes skin irritation
 H317 - May cause an allergic skin reaction
 H319 - Causes serious eye irritation
 H332 - Harmful if inhaled
 H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
 H335 - May cause respiratory irritation
 H351 - Suspected of causing cancer.
 H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

- Prevention** • P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P260 - Do not breathe mist/vapours/spray.
 P264 - Wash thoroughly after handling.
 P271 - Use only outdoors or in a well-ventilated area.
 P272 - Contaminated work clothing should not be allowed out of the workplace.
 P280 - Wear protective gloves, clothing, and eye/face protection, .
 P281 - Use personal protective equipment as required.
 P285 - In case of inadequate ventilation wear respiratory protection.
- Response** • P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
 P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
 P321 - Specific treatment, see supplemental first aid information.
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P362 - Take off contaminated clothing and wash before reuse.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P308+P313 - IF exposed or concerned: Get medical advice/attention.
 P314 - Get medical advice/attention if you feel unwell.

- Storage/Disposal** • P403+P233 - Store in a well-ventilated place. Keep container tightly closed. Keep away from moisture.
 P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

- Supplemental information** • 59 percent of this product consists of an ingredient of unknown toxicity.

DSD/DPD



- Risk phrases** • R20 - Harmful by inhalation.
 R36/37/38 - Irritating to eyes, respiratory system and skin.
 R40 - Limited evidence of a carcinogenic effect.
 R42/43 - May cause sensitisation by inhalation and skin contact.
 R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.

- Safety phrases** • S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 S36 - Wear suitable protective clothing.
 S37 - Wear suitable gloves.
 S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
 S53 - Avoid exposure - obtain special instructions before use.

2.3 Other Hazards

CLP

- According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

DSD/DPD

- According to European Directive 1999/45/EC this preparation is considered dangerous.

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

OSHA HCS 2012

- Skin Irritation 2
- Skin Sensitization 1A
- Eye Irritation 2
- Respiratory Sensitization 1A
- Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
- Specific Target Organ Toxicity Repeated Exposure 1

2.2 Label elements

OSHA HCS 2012

DANGER



- Hazard statements**
- Causes skin irritation
 - May cause an allergic skin reaction
 - Causes serious eye irritation
 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
 - May cause respiratory irritation
 - Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

- Prevention**
- Do not breathe mist/vapours/spray.
 - Wash thoroughly after handling.
 - Do not eat, drink or smoke when using this product.
 - Use only outdoors or in a well-ventilated area.
 - Contaminated work clothing should not be allowed out of the workplace.
 - Wear protective gloves, clothing, and eye/face protection.
 - In case of inadequate ventilation wear respiratory protection.
- Response**
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
 - If on skin: Wash with plenty of water.
 - Specific treatment, see supplemental first aid information.
 - If skin irritation or rash occurs: Get medical advice/attention.
 - Take off contaminated clothing and wash before reuse.
 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - If eye irritation persists: Get medical advice/attention.
 - Get medical advice/attention if you feel unwell.
- Storage/Disposal**
- Store in a well-ventilated place. Keep container tightly closed.
 - Keep away from moisture.
 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

2.3 Other hazards

OSHA HCS 2012

- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to: WHMIS

2.1 Classification of the substance or mixture

WHMIS

- Very Toxic - D1A
Other Toxic Effects - D2A
Other Toxic Effects - D2B

2.2 Label elements**WHMIS****WHMIS**

- Very Toxic - D1A
Other Toxic Effects - D2A
Other Toxic Effects - D2B

2.3 Other hazards**WHMIS**

- In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients**3.1 Substances**

- Material does not meet the criteria of a substance.

3.2 Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Isocyanic acid, methylenedi-p-phenylene ester	CAS: 101-68-8 EC Number: 202-966-0 EU Index: 615-005-00-9	20% TO 40%	Ingestion/Oral-Rat LD50 • 9200 mg/kg Inhalation-Rat LC50 • 178 mg/m ³	EU DSD/DPD: Annex VI, Table 3.2: Carc. Cat. 3; R40; Xn R20-48/20; Xi R36/37/38 R42/43 EU CLP: Annex VI, Table 3.1: Carc. 2, H351; Acute Tox. 4, H332; STOT RE 2, H373; Eye Irrit. 2, H319; Skin Irrit. 2, H315; STOT SE 3, H335; Resp. Sens. 1, H334; Skin Sens. 1, H317 OSHA HCS 2012: Eye Irrit. 2; Skin Irrit. 2; Skin Sens. 1A; STOT SE 3: Resp. Irrit.; Resp. Sens. 1A; STOT RE 1 (Lungs);	NDA
Siloxanes and Silicones, di-Me, reaction products with silica	CAS: 67762-90-7	1% TO 5%	NDA	EU DSD/DPD: Not Classified EU CLP: Not Classified OSHA HCS 2012: Not Classified	NDA
Propane, 1,2-epoxy-	CAS: 75-56-9 EC Number: 200-879-2 EU Index: 603-055-00-4	< 0.1%	Ingestion/Oral-Rat LD50 • 380 mg/kg Inhalation-Rat LC50 • 4000 ppm 4 Hour(s) Skin-Rabbit LD50 • 1500 µL/kg	EU CLP: Community workplace exposure limit OSHA HCS 2012: Exposure limits	NDA
Furan	CAS: 110-00-9 EC Number: 203-727-3 EU Index: 603-105-00-5	< 0.1%	NDA	EU CLP: Community workplace exposure limit OSHA HCS 2012: Exposure limits	NDA
	CAS: 7440-48-4				

Cobalt	EC Number:231-158-0 EU Index:027-001-00-9	< 0.1%	Ingestion/Oral-Rat LD50 • 6171 mg/kg	EU CLP: Community workplace exposure limit OSHA HCS 2012: Exposure limits	NDA
Acetaldehyde	CAS:75-07-0 EC Number:200-836-8 EU Index:605-003-00-6	< 0.1%	Ingestion/Oral-Rat LD50 • 661 mg/kg Inhalation-Rat LC50 • 13300 ppm 4 Hour(s) Skin-Rabbit LD50 • 3540 mg/kg	EU CLP: Community workplace exposure limit OSHA HCS 2012: Exposure limits	NDA

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

- Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Get medical attention immediately.

Skin

- Remove contaminated clothing and shoes. Wash immediately with soap and water for at least 15 minutes. Discard contaminated shoes and clothing. If irritation develops and persists, get medical attention.

Eye

- Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. If eye irritation persists: Get medical advice/attention.

Ingestion

- Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media • Carbon Dioxide, Dry Chemical, Foam.

Unsuitable Extinguishing Media • Do not use water.

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

- Reacts with water and emits carbon dioxide gas. Exposure to water will initiate reaction, which may be violent. The product is not flammable. However, it will burn if strongly heated and when involved in fire.

Hazardous Combustion Products

- Carbon oxides. Nitrogen oxides. Hydrocarbons. Isocyanates.

5.3 Advice for firefighters

- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible. Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Wear positive pressure self-contained breathing apparatus (SCBA).
Move containers from fire area if you can do it without risk.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

- Ventilate enclosed areas. Do not walk through spilled material. Wear appropriate personal protective equipment, avoid direct contact. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Emergency Procedures

- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stay upwind. Keep out of low areas. Keep unauthorized personnel away. Ventilate closed spaces before entering.

6.2 Environmental precautions

- Avoid release to the environment.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

- Stop leak if you can do it without risk.
Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
LARGE SPILLS: Dike far ahead of spill for later disposal.
Never return spills in original containers for re-use.

6.4 Reference to other sections

- Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

- Use only in well ventilated areas. Use good safety and industrial hygiene practices. Wear appropriate personal protective equipment, avoid direct contact. Do not breath mist/vapours/spray. Avoid contact with skin, eyes, and clothing. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

7.2 Conditions for safe storage, including any incompatibilities

Storage

- Keep container tightly closed. Store in a cool, dry, well-ventilated place. Keep away from incompatible materials.

7.3 Specific end use(s)

- Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines						
	Result	ACGIH	Canada Alberta	Canada British Columbia	Canada Manitoba	Canada New Brunswick
Acetaldehyde (75-07-0)	Ceilings	25 ppm Ceiling	25 ppm Ceiling; 45 mg/m ³ Ceiling	25 ppm Ceiling	25 ppm Ceiling	25 ppm Ceiling; 45 mg/m ³ Ceiling
Propane, 1,2-epoxy - (75-56-9)	TWAs	2 ppm TWA	2 ppm TWA; 4.7 mg/m ³ TWA	2 ppm TWA	2 ppm TWA	20 ppm TWA; 48 mg/m ³ TWA
Cobalt (7440-48-4)	TWAs	0.02 mg/m ³ TWA	0.02 mg/m ³ TWA	0.02 mg/m ³ TWA	0.02 mg/m ³ TWA	0.02 mg/m ³ TWA

Isocyanic acid, methylenedi-p-phenylene ester (101-68-8)	TWAs	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate (MDI))	0.005 ppm TWA; 0.05 mg/m3 TWA	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate (MDI))	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate (MDI))	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate); 0.051 mg/m3 TWA (listed under Methylene bisphenyl isocyanate)
	Ceilings	Not established	Not established	0.01 ppm Ceiling (listed under Methylene bisphenyl isocyanate (MDI))	Not established	Not established

Exposure Limits/Guidelines (Con't.)

	Result	Canada Northwest Territories	Canada Nova Scotia	Canada Nunavut	Canada Ontario	Canada Quebec
Acetaldehyde (75-07-0)	STELs	150 ppm STEL; 270 mg/m3 STEL	Not established	150 ppm STEL; 270 mg/m3 STEL	Not established	Not established
	TWAs	100 ppm TWA; 180 mg/m3 TWA	Not established	100 ppm TWA; 180 mg/m3 TWA	Not established	Not established
	Ceilings	Not established	25 ppm Ceiling	Not established	25 ppm Ceiling	25 ppm Ceiling; 45 mg/m3 Ceiling
Propane, 1,2-epoxy (75-56-9)	STELs	30 ppm STEL; 71 mg/m3 STEL	Not established	30 ppm STEL; 71 mg/m3 STEL	Not established	Not established
	TWAs	20 ppm TWA; 47 mg/m3 TWA	2 ppm TWA	20 ppm TWA; 47 mg/m3 TWA	2 ppm TWA	20 ppm TWA EV; 48 mg/m3 TWA EV
Cobalt (7440-48-4)	STELs	0.3 mg/m3 STEL (dust and fume)	Not established	0.3 mg/m3 STEL (dust and fume)	Not established	Not established
	TWAs	0.1 mg/m3 TWA (dust and fume)	0.02 mg/m3 TWA	0.1 mg/m3 TWA (metal, dust and fume)	0.02 mg/m3 TWA	0.02 mg/m3 TWA EV
Isocyanic acid, methylenedi-p-phenylene ester (101-68-8)	TWAs	Not established	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate (MDI))	Not established	0.005 ppm TWA (designated substances regulation, listed under Isocyanates, organic compounds (Methylene bisphenyl isocyanate (MDI))); 0.005 ppm TWA (applies to workplaces to which the designated substances regulation does not apply, listed under Methylene bisphenyl isocyanate (MDI))	0.005 ppm TWA EV; 0.051 mg/m3 TWA EV
	Ceilings	Not established	Not established	Not established	0.02 ppm Ceiling (designated substances regulation, listed under Isocyanates, organic compounds (Methylene bisphenyl isocyanate (MDI)))	Not established

Exposure Limits/Guidelines (Con't.)					
	Result	Canada Saskatchewan	Canada Yukon	NIOSH	OSHA
Acetaldehyde (75-07-0)	STELs	Not established	150 ppm STEL; 270 mg/m ³ STEL	Not established	Not established
	TWAs	Not established	100 ppm TWA; 180 mg/m ³ TWA	Not established	200 ppm TWA; 360 mg/m ³ TWA
Propane, 1,2-epoxy- (75-56-9)	TWAs	2 ppm TWA	100 ppm TWA; 240 mg/m ³ TWA	Not established	100 ppm TWA; 240 mg/m ³ TWA
	STELs	Not established	150 ppm STEL; 360 mg/m ³ STEL	Not established	Not established
Cobalt (7440-48-4)	TWAs	0.02 mg/m ³ TWA	0.05 mg/m ³ TWA (dust and fume)	0.05 mg/m ³ TWA (dust and fume)	0.1 mg/m ³ TWA (dust and fume)
	STELs	Not established	0.15 mg/m ³ STEL (dust and fume)	Not established	Not established
Isocyanic acid, methylenedi-p-phenylene ester (101-68-8)	TWAs	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate (MDI))	Not established	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate); 0.05 mg/m ³ TWA	Not established
	Ceilings	Not established	0.02 ppm Ceiling (Methylene bisphenyl isocyanate (MDI)); 0.2 mg/m ³ Ceiling (Methylene bisphenyl isocyanate (MDI))	0.020 ppm Ceiling (10 min); 0.2 mg/m ³ Ceiling (10 min)	0.02 ppm Ceiling; 0.2 mg/m ³ Ceiling

Exposure Control Notations

Canada Ontario

• Isocyanic acid, methylenedi-p-phenylene ester (101-68-8): **Designated Substances:** (0.005 ppm TWA (listed under Isocyanates, organic compounds (Methylene bisphenyl isocyanate (MDI))); 0.02 ppm Ceiling (listed under Isocyanates, organic compounds (Methylene bisphenyl isocyanate (MDI))))

Canada Quebec

- Acetaldehyde (75-07-0): **Carcinogens:** (C3 carcinogen - effect detected in animals)
- Cobalt (7440-48-4): **Carcinogens:** (C3 carcinogen - effect detected in animals)
- Propane, 1,2-epoxy- (75-56-9): **Carcinogens:** (C2 carcinogen - effect suspected in humans)

ACGIH

- Acetaldehyde (75-07-0): **Carcinogens:** (A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans)
- Cobalt (7440-48-4): **Carcinogens:** (A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans)
- Propane, 1,2-epoxy- (75-56-9): **Carcinogens:** (A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans) | **Sensitizers:** (Sensitizer)

Exposure Limits Supplemental

ACGIH

- Isocyanic acid, methylenedi-p-phenylene ester (101-68-8): **TLV Basis - Critical Effects:** (respiratory sensitization (listed under Methylene bisphenyl isocyanate (MDI)))
- Acetaldehyde (75-07-0): **TLV Basis - Critical Effects:** (eye and upper respiratory tract irritation) | **Notice of Intended Changes (TLVs):** (25 ppm Ceiling; A2 - suspected human carcinogen; TLV basis: eye and upper respiratory tract irritation)
- Cobalt (7440-48-4): **BEIs:** (15 µg/L Medium: urine Time: end of shift at end of workweek Parameter: Cobalt (background); 1 µg/L Medium: blood Time: end of shift at end of workweek Parameter: Cobalt (background, semi-quantitative)) | **TLV Basis - Critical Effects:** (asthma; myocardial effects; pulmonary function)
- Propane, 1,2-epoxy- (75-56-9): **TLV Basis - Critical Effects:** (eye and upper respiratory tract irritation) | **Notice of Intended Changes (TLVs):** (Proposed update of SEN notation to DSEN to indicate dermal sensitizer)

8.2 Exposure controls

Engineering Measures/Controls

- This material is designed to be used outdoors, in roofing applications. Good general ventilation should be used. Ventilation rates should be matched to conditions. If

applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Respiratory

- In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

- Wear safety goggles. Use face shield in case of splash risk.

Skin/Body

- Wear chemical-resistant gloves, footwear and protective clothing appropriate for risk of exposure.

Environmental Exposure Controls

- In case of spills, keep product clear of sewers, waterways or land areas. Dispose of waste product in accordance with national and local laws and regulations.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

STEL = Short Term Exposure Limits are based on 15-minute exposures

BEI = Biological Exposure Indices

TLV = Threshold Limit Value determined by the American Conference of Governmental Industrial Hygienists (ACGIH)

MSHA = Mine Safety and Health Administration

TWAEV = Time-Weighted Average Exposure Value

NIOSH = National Institute of Occupational Safety and Health

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

OSHA = Occupational Safety and Health Administration

Section 9 - Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Tan viscous liquid with faint aromatic odor.
Color	Tan	Odor	Faint Aromatic.
Odor Threshold	Data lacking		
General Properties			
Boiling Point	Data lacking	Melting Point/Freezing Point	Not relevant
Decomposition Temperature	Data lacking	pH	Data lacking
Specific Gravity/Relative Density	= 1.1 Water=1	Water Solubility	Exposure to water will initiate reaction, which may be violent.
Viscosity	6700 Centipoise (cPs, cP) or mPas @ 75 °F(23.8889 °C)	Explosive Properties	Data lacking
Oxidizing Properties:	Data lacking		
Volatility			
Vapor Pressure	Data lacking	Vapor Density	Data lacking
Evaporation Rate	Data lacking	Volatiles (Wt.)	< 0.15 %
Volatiles (Vol.)	< 0.15 %		
Flammability			
Flash Point	> 199.4 °F(> 93 °C) PMCC (Pensky-Martins Closed Cup)	UEL	Data lacking
LEL	Data lacking	Autoignition	Data lacking
Flammability (solid, gas)	Data lacking		
Environmental			

Octanol/Water Partition coefficient	Data lacking		
-------------------------------------	--------------	--	--

9.2 Other Information

- No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

- Exposure to water will initiate reaction, which may be violent. CO₂ gas is produced.

10.2 Chemical stability

- Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

- Hazardous polymerization will not occur.

10.4 Conditions to avoid

- Keep away from heat, sparks and flame.

10.5 Incompatible materials

- Water. Alcohol. Alkaline metals. Acids. Bases.

10.6 Hazardous decomposition products

- None known.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Components		
Isocyanic acid, methylenedi-p-phenylene ester (20% TO 40%)	101-68-8	Acute Toxicity: Ingestion/Oral-Rat LD50 • 9200 mg/kg; Behavioral:Somnolence (general depressed activity); Behavioral:Ataxia; Nutritional and Gross Metabolic:Changes in Chemistry or Temperature:Body temperature decrease; Inhalation-Rat TClO • 2.4 mg/m ³ 6 Hour(s); Lungs, Thorax, or Respiration:Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration:Other changes; Biochemical:Metabolism (intermediary):Other proteins; Irritation: Eye-Rabbit • 100 mg • Moderate irritation; Skin-Rabbit • 500 mg 24 Hour(s)
Siloxanes and Silicones, di-Me, reaction products with silica (1% TO 5%)	67762-90-7	Multi-dose Toxicity: Inhalation-Rat TClO • 30 mg/kg 6 Hour(s) 4 Week(s)-Intermittent; Lungs, Thorax, or Respiration:Other changes; Blood:Hemorrhage; Related to Chronic Data:Death in the Other Multiple Dose data type field

GHS Properties	Classification
Acute toxicity	EU/CLP • Acute Toxicity - Inhalation 4 - ATEmix(inhl) = 1.537 mg/L OSHA HCS 2012 • Data lacking
Skin corrosion/Irritation	EU/CLP • Skin Irritation 2 OSHA HCS 2012 • Skin Irritation 2
Serious eye damage/Irritation	EU/CLP • Eye Irritation 2 OSHA HCS 2012 • Eye Irritation 2
Skin sensitization	EU/CLP • Skin Sensitizer 1 OSHA HCS 2012 • Skin Sensitizer 1A

Respiratory sensitization	EU/CLP • Respiratory Sensitizer 1 OSHA HCS 2012 • Respiratory Sensitizer 1A
Aspiration Hazard	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Carcinogenicity	EU/CLP • Carcinogenicity 2 OSHA HCS 2012 • Data lacking
Germ Cell Mutagenicity	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Toxicity for Reproduction	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
STOT-SE	EU/CLP • Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
STOT-RE	EU/CLP • Specific Target Organ Toxicity Repeated Exposure 2 OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 1

Potential Health Effects

Inhalation

Acute (Immediate)

- Harmful if inhaled. May cause respiratory irritation.

Chronic (Delayed)

- Vapors can induce respiratory allergic sensitization with asthma-like symptoms. Symptoms include chronic cough, tightness of chest with difficulty in breathing. These symptoms may be immediate or delayed up to several hours after exposure.

Skin

Acute (Immediate)

- Causes skin irritation. May cause skin sensitization. Symptoms include redness, and skin rash.

Chronic (Delayed)

- No data available

Eye

Acute (Immediate)

- Causes serious eye irritation.

Chronic (Delayed)

- No data available.

Ingestion

Acute (Immediate)

- Ingestion may cause vomiting, nausea, diarrhea, or other systemic effects.

Chronic (Delayed)

- No data available.

Other

Chronic (Delayed)

- Long-term effect of Isocyanic acid, methylenedi-p-phenylene ester on the respiratory system of 318 workers suggests that such workers may develop fibrosis. Long-term exposure tends to restrict pulmonary function and cause decrease in CO single breath transfer factor.

Carcinogenic Effects

- Repeated and prolonged exposure may cause cancer.

Carcinogenic Effects			
	CAS	IARC	NTP
Acetaldehyde	75-07-0	Group 1-Carcinogenic	Reasonably Anticipated to be Human Carcinogen
Cobalt	7440-48-4	Group 2B-Possible Carcinogen	Not Listed
Furan	110-00-9	Group 2B-Possible Carcinogen	Reasonably Anticipated to be Human Carcinogen
Propane, 1,2-epoxy-	75-56-9	Group 2B-Possible Carcinogen	Reasonably Anticipated to be Human Carcinogen

Key to abbreviations

LD = Lethal Dose

TC = Toxic Concentration

Section 12 - Ecological Information

12.1 Toxicity

	CAS	
FillGard™ M Pourable Sealer Part A	NDA	<p>Aquatic Toxicity-Fish: 96 Hour(s) LC50 200 mg/L Comments: Ethylenediamine, N-(3-(trimethoxysilyl)propyl)- 96 Hour(s) LC50 >100 mg/L Comments: 2(2-Hydroxy-3,5-diteramylphenyl) benzotriazole 96 Hour(s) LC50 0.97 mg/L Comments: Bis(1-2,2,5,6-pentamethyl-4-piperdiny)decanoate</p> <p>Aquatic Toxicity-Crustacea: 24 Hour(s) EC50 <i>Daphnia</i> 20 mg/L Comments: Bis(1-2,2,5,6-pentamethyl-4-piperdiny)decanoate 24 Hour(s) EC50 <i>Daphnia</i> >100 mg/L Comments: 2(2-Hydroxy-3,5-diteramylphenyl) benzotriazole 48 Hour(s) EC50 <i>Daphnia</i> 90 mg/L Comments: Ethylenediamine, N-(3-(trimethoxysilyl)propyl)-</p> <p>Aquatic Toxicity-Algae and Other Aquatic Plant(s): 96 Hour(s) EC50 Algae 11 mg/L Comments: Ethylenediamine, N-(3-(trimethoxysilyl)propyl)- 72 Hour(s) IC50 Algae >10 mg/L Comments: 2(2-Hydroxy-3,5-diteramylphenyl) benzotriazole</p> <p>Aquatic Toxicity-Other: 3 Hour(s) EC50 <i>Bacteria</i> >100 mg/L Comments: Bis(1-2,2,5,6-pentamethyl-4-piperdiny)decanoate</p>

- The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

12.2 Persistence and degradability

- Expected to be persistent.

12.3 Bioaccumulative potential

- Not expected to bioaccumulate.

12.4 Mobility in Soil

- Water reactive material.

12.5 Results of PBT and vPvB assessment

- No PBT and vPvB assessment has been conducted.

12.6 Other adverse effects

- No studies have been found.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	NDA	Not Regulated	NDA	NDA	NDA
TDG	NDA	Not Regulated	NDA	NDA	NDA
IMO/IMDG	NDA	Not Regulated	NDA	NDA	NDA

ADN	NDA	Not Regulated	NDA	NDA	NDA
ADR/RID	NDA	Not Regulated	NDA	NDA	NDA
IATA/ICAO	NDA	Not Regulated	NDA	NDA	NDA

14.6 Special precautions for user • None specified.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code • Data lacking.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Chronic

State Right To Know				
Component	CAS	MA	NJ	PA
Acetaldehyde	75-07-0	Yes	Yes	Yes
Cobalt	7440-48-4	Yes	Yes	Yes
Furan	110-00-9	Yes	Yes	Yes
Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	No	No	Yes
Propane, 1,2-epoxy -	75-56-9	Yes	Yes	Yes
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	No	No	No

Inventory						
Component	CAS	Canada DSL	Canada NDSL	EU EINECS	EU ELNICS	TSCA
Acetaldehyde	75-07-0	Yes	No	Yes	No	Yes
Cobalt	7440-48-4	Yes	No	Yes	No	Yes
Furan	110-00-9	Yes	No	Yes	No	Yes
Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Yes	No	Yes	No	Yes
Propane, 1,2-epoxy -	75-56-9	Yes	No	Yes	No	Yes
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Yes	No	No	No	Yes

Canada

Labor

Canada - WHMIS - Classifications of Substances

• Propane, 1,2-epoxy-	75-56-9	B2, D1B, D2A, D2B
• Furan	110-00-9	B2, D1A, D2A

• Acetaldehyde	75-07-0	B2, D2A
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	D1A, D2A, D2B
• Cobalt	7440-48-4	D2A, D2B
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

Canada - WHMIS - Ingredient Disclosure List

• Propane, 1,2-epoxy-	75-56-9	1 %
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	1 %
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	0.1 %
• Cobalt	7440-48-4	0.1 %
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

Environment**Canada - CEPA - Priority Substances List**

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Priority Substance List 2 (substance considered toxic)
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

Europe**Other****EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification**

• Propane, 1,2-epoxy-	75-56-9	F+; R12 Xn; R20/21/22 Xi; R36/37/38 Carc.Cat.2; R45 Muta.Cat.2; R46
• Furan	110-00-9	F+; R12 R19 Xn; R20/22-48/22 Xi; R38 Carc.Cat.2; R45 R52- 53 Muta.Cat.3; R68
• Acetaldehyde	75-07-0	F+; R12 Xi; R36/37 Carc.Cat.3; R40
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Xn; R20-48/20 Xi; R36/37/38 Carc.Cat.3; R40 R42/43
• Cobalt	7440-48-4	R42/43 R53
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	5%≤C: Xi; R:36/37/38 0.1% ≤C: R:42
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling

• Propane, 1,2-epoxy-	75-56-9	F+ T R:45-46-12-20/21/22- 36/37/38 S:53-45
• Furan	110-00-9	F+ T R:45-12-19-20/22-38- 48/22-68-52/53 S:53-45-61
• Acetaldehyde	75-07-0	F+ Xn R:12-36/37-40 S:(2)-16- 33-36/37

• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Xn R:20-36/37/38-40-42/43-48/20 S:(1/2)-23-36/37-45
• Cobalt	7440-48-4	Xn R:42/43-53 S:(2)-22-24-37-61
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations

• Propane, 1,2-epoxy-	75-56-9	E
• Furan	110-00-9	E
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	C, 2
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases

• Propane, 1,2-epoxy-	75-56-9	S:53-45
• Furan	110-00-9	S:53-45-61
• Acetaldehyde	75-07-0	S:(2)-16-33-36/37
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	S:(1/2)-23-36/37-45
• Cobalt	7440-48-4	S:(2)-22-24-37-61
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	500 lb TQ
• Acetaldehyde	75-07-0	2500 lb TQ
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

• Propane, 1,2-epoxy-	75-56-9	
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	(listed under Methylene diphenyl diisocyanate)
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

• Propane, 1,2-epoxy-	75-56-9	100 lb final RQ; 45.4 kg final RQ
• Furan	110-00-9	100 lb final RQ; 45.4 kg final RQ

• Acetaldehyde	75-07-0	1000 lb final RQ; 454 kg final RQ
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	5000 lb final RQ; 2270 kg final RQ
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed
U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities		
• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed
U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs		
• Propane, 1,2-epoxy-	75-56-9	100 lb EPCRA RQ
• Furan	110-00-9	100 lb EPCRA RQ
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed
U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs		
• Propane, 1,2-epoxy-	75-56-9	10000 lb TPQ
• Furan	110-00-9	500 lb TPQ
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed
U.S. - CERCLA/SARA - Section 313 - Emission Reporting		
• Propane, 1,2-epoxy-	75-56-9	0.1 % de minimis concentration
• Furan	110-00-9	0.1 % de minimis concentration
• Acetaldehyde	75-07-0	0.1 % de minimis concentration
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	1.0 % de minimis concentration (listed under Chemical Category N120, Diisocyanates)
• Cobalt	7440-48-4	0.1 % de minimis concentration
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed
U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing		
• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed
U.S. - RCRA (Resource Conservation & Recovery Act) - Constituents for Detection Monitoring		
• Propane, 1,2-epoxy-	75-56-9	Not Listed

• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	(total)
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

U.S. - RCRA (Resource Conservation & Recovery Act) - List for Hazardous Constituents

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	(total)
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

U.S. - RCRA (Resource Conservation & Recovery Act) - TSD Facilities Ground Water Monitoring

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	(total)
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

U.S. - RCRA (Resource Conservation & Recovery Act) - U Series Wastes - Acutely Toxic Wastes & Other Hazardous Characteristics

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	waste number U124 (Ignitable waste)
• Acetaldehyde	75-07-0	waste number U001 (Ignitable waste)
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

United States - California**Environment****U.S. - California - Proposition 65 - Carcinogens List**

• Propane, 1,2-epoxy-	75-56-9	carcinogen, initial date 10/1/88
• Furan	110-00-9	carcinogen, initial date 10/1/93
• Acetaldehyde	75-07-0	carcinogen, initial date 4/1/88
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	carcinogen, initial date 7/1/92 (powder)
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed

• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed
U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)		
• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	90 µg/day NSRL (inhalation)
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed
U.S. - California - Proposition 65 - Reproductive Toxicity - Female		
• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed
U.S. - California - Proposition 65 - Reproductive Toxicity - Male		
• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

United States - Pennsylvania

Labor

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

• Propane, 1,2-epoxy-	75-56-9	
• Furan	110-00-9	
• Acetaldehyde	75-07-0	
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	
• Cobalt	7440-48-4	
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

• Propane, 1,2-epoxy-	75-56-9	
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

15.2 Chemical Safety Assessment

- No Chemical Safety Assessment has been carried out.

15.3 Other Information

- **WARNING:** This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

- Revision Date**
- 24/January/2018
- Preparation Date**
- 18/October/2011
- Other Information**
- Changes to this revision: Updated mailing address.
- Disclaimer/Statement of Liability**
- The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.

Key to abbreviations

NDA = No Data Available